

BRANCHPIPES, HANDLINE NOZZLE AND FIRE HOSE

Kolling manufactures a wide range of branchpipe and nozzles for hydrant systems, water and foam systems.

GENERAL SPECIFICATIONS

Body : Aluminium Alloy to BS 1490/Copper Alloy to BS1400
 Connection Inlet : Male Instantaneous to BS336, ANSI NH-7.5, Round Thread to BS336, Storz and Other International Outlet Fittings Are Available On Request.



Model	Description	Inlet Size
BP401	Jet Nozzle with Branchpipe	2 1/2" (65mm) BS336 Male Inst.
BP402	Diffuser Nozzle (Jet/Spray)	2 1/2" (65mm) BS336 Male Inst.
BP403	Diffuser Nozzle with Branchpipe (Jet/Spray)	2 1/2" (65mm) BS336 Male Inst.
BP406	Fog Nozzle with Branchpipe	2 1/2" (65mm) BS336 Male Inst.
BP407	Jet/Spray Nozzle with Branchpipe	1 1/2" (38mm) BS336 Male Inst.
BP408	Jet Nozzle With Ball Control Valve	1 1/2" BSP or NST
BP409	Jet/Spray Nozzle	1" Female NST, 1 1/2" Female NST, 2 1/2" Female NST
SPP9524	Jet/Spray Pistol Grip Nozzle	1 1/2", 2 1/2", NHT or 2 1/2" BS336 Male Inst.

SELECTABLE GALLONAGE HANDLINE NOZZLE



The selectable gallonage handline nozzle is an easy to operate combination pattern nozzle with versatile multiple flow setting. The nozzle produces straight stream for maximum reach and wide fog pattern for optimum performance. We strive to ensure quality standards on our products as well as products we distribute from other manufacturer to meet the same standards. Protek Fire, a fire hose specialist has the the wide range of products to meet the industry needs. Available Brand: Kolling / Protek.

HANDLINE NOZZLE

Model	Description	Connection
#366	30-60-95-125 GPM (115-230-360-475 L/min)	1 1/2", 2 1/2" NH or 2 1/2" Male Inst.
#368	95-125-150-200-250 GPM (360-475-550-750-950 L/min)	1 1/2", 2 1/2" NH or 2 1/2" Male Inst.
#KM2	40-80-106-127 GPM (150-300-400-480 L/min)	1 1/2", 2 1/2" NH or Male Inst.



LAYFLAT TYPE FIRE HOSES



FIRE HOSE, TYPE 1

The type 1 layflat fire hoses are constructed with internal rubber lining combine with closely woven polyester fibre for exceptional strength. Process includes direct vulcanization achieving high adhesion between jacket and lining.

GENERAL SPECIFICATIONS

Size	: 1 1/2" (38mm) or 2 1/2" (65mm)
Standard Length	: 30 meters.
Conform to standard	: UL / BS 6391, Type 1
Working Pressure	: 10 Bar, 13 Bar and 17 Bar
Colour	: White
Model	: KFH38/30-T1 / KFH65/30-T1
Available Brand	: Kolling/Pyroprotect/Pyroflex/Syntex Unidur
Available Approval	: Wheelmark / UL



FIRE HOSE, TYPE 3

The type 3 layflat fire hoses are constructed with smooth inner unified lining of specially formulated polymer, high tenacity synthetic fibre circular woven seamless reinforcement and totally encapsulated in all synthetic specially formulated form of Polymer, Extruded, Ribbed cover. It unique features include resistant to heat, weather, abrasion, oil and chemical.

GENERAL SPECIFICATIONS

Size	: 1 1/2" (38mm) / 1 3/4" (45mm) / 2 1/2"(65mm)
Standard Length	: 30 meters.
Conform to standard	: UL / BS 6391, Type 3
Working Pressure	: 17 Bar
Colour	: Red
Model	: KFH38/30-T1 / KFH65/30-T1
Available Brand	: Kolling/Pyroprotect/Pyroflex/Syntex Unidur
Available Approval	: Wheelmark / UL



Hose connection available in BS336, ANSI NH-7.5, Storz and Other International Outlet Fittings Are Available On Request.



Storz



NHT



Gost/TCVN



BS336

NON-COLLAPSIBLE TYPE FIRE AND UTILITY HOSE

The Fire and Utility Hose from KOLLING is a versatile multi-purpose hose suitable for both air and water services. The hoses are constructed standard with internal rubber liner, reinforced with piles of high strength synthetic polyester and complete with a smooth outer surface for exceptional strength and performance. It unique features includes resistant to weather, oil and abrasions with optional wrapped surfaced.

GENERAL SPECIFICATIONS

Size	: 1" (25mm), 1 1/2" (38mm), 1 3/4" (44.5mm) or 2 1/2" (65mm)
Standard Length	: 30 meters
Working Pressure	: 10 Bar / 20 Bar
Burst Pressure	: 60 Bar
Colour	: Black / Red
Temperature Range	: -20 Deg. C to + 80 Deg C
Safety Factor	: 3 : 1

